



WILLIAM JOHNSTON & COMPANY LIMITED

Glasgow Tel: +44 (0) 141 620 1666 | Inverness Tel: +44 (0) 1463 238 673
sales@williamjohnston.co.uk | www.williamjohnston.co.uk

Orange Open Cell Sponge



SPONGE RUBBER
NATURAL
OPEN CELL
WJ160M
160 den orange sponge rubber.
Density 160 kg/m³
Tensile 0.23 N/mm
Elongation 480 %
Hardness Medium.



SPONGE RUBBER
NATURAL
OPEN CELL
WJ200F
200 den orange sponge rubber.
Density 200 kg/m³
Tensile 0.22 N/mm
Elongation 495 %
Hardness Medium.



SPONGE RUBBER
NATURAL
OPEN CELL
WJ200M
200 den orange sponge rubber.
Density 200 kg/m³
Tensile 0.22 N/mm²
Elongation 495 %
Hardness Medium.



SPONGE RUBBER
NATURAL
OPEN CELL
WJ250F
250 den orange sponge rubber.
Density 250 kg/m³
Tensile 0.45 N/mm
Elongation 480 %
Hardness Firm.



SPONGE RUBBER
NATURAL
OPEN CELL
WJ300F
300 den orange sponge rubber.
Density 300 kg/m³
Tensile 0.54 N/mm
Elongation 480 %
Hardness Very firm.



SPONGE RUBBER
NATURAL
OPEN CELL
WJ350F
350 den orange sponge rubber.
Density 350 kg/m³
Tensile 0.65 N/mm
Elongation 470 %
Hardness Hard.



SPONGE RUBBER
NATURAL
OPEN CELL
WJ350FB
350 den blue sponge rubber.
Density 350 kg/m³
Tensile 0.65 N/mm²
Elongation 470 %
Hardness Hard.



SPONGE RUBBER
NATURAL
OPEN CELL
WJ600F
600 den orange sponge rubber.
Density 600 kg/m³
Tensile 1.2 N/mm²
Elongation 460 %
Hardness Very Hard.

Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.